



Building on quality

'M' range flexible shaft pokers

Pokers of the highest quality, giving exceptional reliability. Often preferred by hire companies and specified by concreting contractors

Highest Quality

- Made in Sheffield, quality you can rely on
- Triple sealed head, protecting the precision engineering
- Double bearings, for a longer working life triple bearings on 281 poker
- Components heat treated and hardened, minimum wear
- Interchangeable shafts, quicker repairs, bespoke shaft lengths
- Coupling choice, suitable for any make of poker unit

For a complete poker, choose your poker head, shaft length and coupling from the table.

* 50 and 65mm pokers are supplied fitted with a stress relieving shaft sleeve.

| | Diameter mm | Length mm | Amplitude mm | Frequency V.P.M. | Weight KG c/w 5 m shaft | HAV m/sec ² | Order Code |
|---|---|-----------|--------------|------------------|-------------------------|------------------------|------------|
| 281 'M' range poker head | 28 | 390 | 0.7 | 20,000 | 14.3 | 2 | 92106 |
| 385 'M' range poker head | 38 | 470 | 0.8 | 17,000 | 20.7 | 5 | 92013 |
| 501 'M' range poker head | 50 | 1100* | 1.8 | 14,000 | 25.4 | 4 | 92019 |
| 651 'M' range poker head | 65 | 1150* | 2.6 | 13,000 | 27.4 | 3 | 92031 |
| 3m Flexible drive for 281 head | 27 | 3m | | | | | 92111 |
| 5m Flexible drive for 281 head | 27 | 5m | | | | | 92287 |
| 6m Flexible drive for 281 head | 27 | 6m | | | | | 92492 |
| 3m Flexible drive for 385,501 & 651 heads | 32 | 3m | | | | | 92040 |
| 5m Flexible drive for 385,501 & 651 heads | 32 | 5m | | | | | 92067 |
| 6m Flexible drive for 385,501 & 651 heads | 32 | 6m | | | | | 92215 |
| 8m Flexible drive for 385,501 & 651 heads | 32 | 8m | | | | | 92642 |
| Metrix "Standard" coupling | For Metrix "standard" coupling drive units | | | | | | 92050 |
| "Dynapac" type coupling | For Errut/Belle, CEL, Dynapac, Winget, Wacker drive units | | | | | | 92051 |
| "Warsop" type coupling | For Warsop type drive units | | | | | | 92283 |