

GOODENOUGH PUMPS



FAIRPORT

Building on quality

Submersible Flexible Shaft driven Pump

A submersible with a difference. TFE powered by your flexible shaft (poker) drive unit, there's no better way to drain footings before the concrete goes in.

Improved Utilisation

- The advantages of a submersible without being electric
- No motor, extremely low maintenance
- TFE 2" or 3" Output, accepts standard hoses
- No priming, No sparks, No smell
- Reliable, the pumps can left running unattended for extended periods

A Flexible shaft driven pump in cast aluminium, fitted with a steel wear plate. The impeller is cast iron and of the semi open type capable of handling solids up to 8mm bearing are protected by 3 lip seals running on a stainless steel replaceable sleeve the pump is fitted with a 5 metre flexible drive as standard.

Supplied with 5m flexible shaft and coupling, select and order the correct coupling

	Head		Flow @ 2800 RPM		Flow @ 3300 RPM		Flow @ 3600 RPM		Weight Kg	Order Code
	ft	m	G.P.M.	m ³ /hr	G.P.M.	m ³ /hr	G.P.M.	m ³ /hr		
TFE 50/75 Flexible shaft submersible pump	0	0	70	19.1	84	22.9	91	24.8		92890
	10	3	61	16.6	78	21.3	85	23.2		
	20	6	46	12.5	69	18.8	76	20.7		
	30	9	19	5.2	53	14.5	62	16.9		
	40	12			28	7.6	44	12		
	50	15					20	5.5		
2" Layflat hose 10m										W17107
3" Layflat hose 10m										W17108
Errut/Belle coupling	For Errut/Belle drive units									W60802
Metrix coupling	For Metrix "standard" coupling drive units									92844
Dynapac coupling	For CEL, Dynapac, Winget, Wacker drive units									W60801
Standard W range coupling	For Warsop type drive units									W60803